




## PRIMAFLEX UNI M2L

Specifically for conducting air in railway vehicles. Fulfils many different fire standards. Non-flammable, very lightweight air transport hose, specially manufactured quality product made of high-quality raw material. For universal use in the medium temperature range for hot and cold air. Developed to fulfil high fire protection standards and for use in areas with fire hazards.



# PRIMAFLEX UNI M2L

## CHARACTERISTICS

- Double-layered
- Smooth on the inside
- Good flow characteristics
- Flame-retardant
- Highly cold-resistant
- Highly flexible also in cold temperatures
- Very lightweight
- Kink-proof
- Small bending radiuses

## APPLICATION EXAMPLES

Highly flame-retardant hoses, weld smoke extraction, F1-approval, FAR-approval, automobile manufacturing, railway, conducting hot and cold air, air-conditioning and ventilation technology, railway vehicle construction - air conditioning, railway air conditioning, DIN 45545-2, DIN 5510 BS, M1

Inner diameter (mm)	Outer diameter (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Standard length (m)	Price (€/m)	Article No.
19	22	19	1,700	0,530	0,110	2,5		1061019
22	25	22	1,700	0,530	0,170	2,5		1061022
25	30	25	1,700	0,530	0,185	4		1061025
32	36	32	1,600	0,500	0,280	4		1061032
38	43	38	1,400	0,500	0,305	4		1061038
41	46	44	1,400	0,500	0,310	4		1061041
44	49	44	1,300	0,500	0,320	4		1061044
51	56	51	1,200	0,440	0,360	4		1061051
57	62	57	1,200	0,400	0,450	4		1061057
60	65	60	1,200	0,400	0,460	4		1061060
63	68	63	1,100	0,400	0,485	4		1061063
65	70	63	1,100	0,400	0,520	4		1061065
70	75	70	1,100	0,350	0,540	4		1061070
76	81	76	1,100	0,350	0,580	4		1061076
80	85	80	1,100	0,350	0,605	4		1061080
83	88	83	1,100	0,260	0,630	4		1061083
89	94	89	1,100	0,260	0,690	4		1061089
95	100	95	1,100	0,260	0,730	4		1061095
102	107	102	0,900	0,260	0,770	4		1061102
110	116	110	0,900	0,200	0,820	4		1061110
114	120	114	0,900	0,200	0,845	4		1061114
121	127	121	0,900	0,180	0,885	4		1061121
127	133	127	0,900	0,160	0,925	4		1061127
140	146	140	0,800	0,150	1,000	4		1061140
152	158	152	0,800	0,140	1,200	4		1061152
160	166	160	0,800	0,130	1,300	4		1061160
165	171	165	0,800	0,120	1,380	4		1061165
178	184	178	0,700	0,100	1,430	4		1061178
203	209	203	0,500	0,070	1,650	4		1061203
229	235	229	0,500	0,060	1,850	4		1061229
254	260	254	0,400	0,050	2,090	4		1061254
305	311	305	0,100	0,030	2,610	4		1061305

Other dimensions upon request.  
Measured at +20 °C ambient temperature.

All specifications subject to change without prior notice.  
Our General Terms and Conditions apply.  
Prices are exclusive of VAT.

## ACCESSORIES

